



RVC477190



#### Optional accessories

RA430100:

Storage container with lid, anthracite

RVA016701:

Ethylene absorber starter kit

RVA016801:

Ethylene absorber refill kit

RVA438040:

Bottle support, oak wood, 1 pcs.

RVA450220:

Activated charcoal air filter, 2 pcs

#### Installation accessories

RA425110:

Vario SS handle 1131 mm

RA460020:

Frontpanel connection long

RVA421722:

SS door with handle 76.2 cm (30")

RVA423141:

Side trims, 3 mm

RVA428722:

SS door w/o handle 76.2 cm (30")

RVA460000:

Installationskit side-by-side

RVA460020:

Backward compatibility kit SbS

RVA466700:

Door direction change kit 76.2 cm (30")

refrigerator Vario cooling Expressive series  
213.4 x 76.2 cm

RVC477190

- Professional freshness system with four different climate zones, even for storing cold-sensitive food.
- Design your ideal cooling system with multiple combination options
- Guided interaction via intuitive touch display
- Opening assist for door enabling seamless integration without handles
- Warm white and glare-free LED light concept for optimal food presentation

#### Highlights

Dark brushed stainless steel interior, refined with solid anthracite aluminium elements.

Warm white and glare-free LED light concept for optimal food presentation in all compartments.

Opening assist for door with two options:

1. Push-to-open function for integration into handleless furniture front
2. Pull-to-open function to facilitate opening the door using a handle

The drawers in the RVC and RVF models are positioned at the same height. With side-by-side installation, the glass shelves and door racks can be aligned on the same level.

Flexible positioning of shelves and door racks through hidden rail system.

Flat dark brushed stainless steel inner door.

Professional freshness system with 2 fresh climate drawers and 1 chilled drawer.

Full touch TFT display.

Total volume: 512 litres.

#### Handling

Opening assist for door.

Cushioned door closing system.

User guidance through light and display response to drawer interaction.

Automatic brightness adjustment based on ambient illumination.

Easy accessible full touch TFT display with clear text.

Animated quick guides to assist appliance maintenance.

#### Technical features

Dynamic cold air distribution.

Automatic defrosting with defrost water evaporation.

Constant air purification by 2 activated charcoal air filters.

Rest mode certified by Star-K.

When rest mode is active, the appliance can only be opened using a handle.

Open-door and malfunction alarm.

#### Selected digital services (Gaggenau Home Connect)

Remote control and monitoring.

Software updates.

Personalisation function for saving custom programmes.

#### Cooling

Professional freshness system.

No-Frost technology with fast cooling.

Temperature adjustable from +2 °C to +8 °C.

3 aluminium-framed safety glass shelves,

individually adjustable in height.

1 integrated safety glass shelf.

Optimal food presentation with warm white and glare-free, hidden LED light bars (3000 K).

Flexible positioning of door racks through hidden rail system.

4 height-adjustable door racks, 1 of which is extra deep.

#### Fresh climate drawer

1 fresh climate drawer with temperature adjustable from -1 °C to +2 °C.

1 fresh climate drawer with temperature adjustable from -1 °C to +8 °C.

Ideal storage conditions for different foods through dedicated programmes (e.g. Fruit, Vegetables, Meat and Cold sensitive food).

Individual adjustment of temperature and humidity.

Extended food preservation with ethylene absorber.

Indirect illumination, transparent front.

Fully extendable, with cushioned closing system.

#### Chilled drawer

Temperature dependent on cooling compartment (always 2K to 3K lower).

Indirect illumination, transparent front.

Fully extendable, with cushioned closing system.

#### Consumption data

Energy efficiency class D at a range of energy efficiency classes from A to G.

Energy consumption 146 kWh/year.

Noise level 38 dB (A) re 1 pW.

#### Planning notes

Flat hinge.

Door hinge right, reversible.


Door opening angle of 115°, fixable at 90°.

Max. door panel weight 41 kg.

#### Connection

Total connected load: 0.300 KW.

Connecting cable 3.0 m, pluggable.




A: Electrical connection  
Maximum door panel dimensions are based on a clearance of 3 mm  
The height of the plinth can be reduced to 50 mm  
Measurements in mm

Niche width 762 mm




The door panel thickness is 19 mm  
The maximum door panel dimensions are based on a clearance of 3 mm, based on a single niche  
Measurements in mm

Niche width 762 mm




The door panel thickness is 19 mm  
The maximum door panel dimensions are based on a clearance of 3 mm, based on a single niche  
Measurements in mm



A: Chilled drawer  
B: Fresh climate drawer  
Measurements in mm

Wall clearance RVB / RVC / RVF / RVW



Niche width

| A   | B   | C1  | C2  |
|-----|-----|-----|-----|
| 457 | 525 | 235 | 265 |
| 610 | 677 | 299 | 330 |
| 762 | 830 | 364 | 395 |
| 900 | 970 | 420 | 442 |

The drawing is based on a door panel thickness of 19 mm as well as the height of a Gaggenau handle of 49 mm

Measurements in mm